The AD-1 System: Distributing high quality audio from a central source to up to 20 remote locations

AD-1 TX Transmitter

AD-1 RX Receiver

The AD-1 System (one transmitter and up to 20 receivers):

- Features a high rate of hum and noise rejection
- Prevents leakage between locations
- Uses high-level balanced line drivers
- Accepts normal "line level" inputs
- Can be "daisy-chained" for easy and fast installation
- Controls output levels at each end
- Is surface-mountable (optional rack panels available)
- Provides stereo outputs for auditoriums and a separate mono output for the lobby
- Receivers employ custom-designed transformers for full isolation

14739 Aurora Ave N, #110 • Shoreline, WA 98133
206.284.9171 • www.componentengineering.com

SPECIFICATIONS

Power Requirements:

Transmitter: 120v ac 50/60 Hz
(220v ac version available)
Receiver: Passive

Frequency Response: 30 to 15 kHz
Separation: 70 dB or better
Distortion: .02% THD

Connectors:

Power: IEC connector
Transmitter audio inputs: Terminal strip/RCA
Receiver audio outputs: Terminal strip

Mounting:

Surface mount
(Rack mount, 1 unit panel adaptor available)

ORDER INFORMATION

Transmitter	AD-1TX (one required for up to 20 receivers)
Receiver	AD-1RX
Rack panel mount kit	AD-1PNL

© Component Engineering, Inc.